

PRODUCT SPECIFICATIONS

135 ROOF LOUVER

1.1 MATERIALS:

- 1.1.1 Aluminum Alloys:** Conform to ASTM B209.
Base: 0.032" Aluminum Coiled Sheet.
Rain Shield: 0.019" Aluminum Coiled Sheet.
Dome: 0.032" Aluminum Coiled Sheet.
- 1.1.2 Galvanized Steel:**
Bracket: 0.061" Galvanized Coiled Sheet.
Screen: 8 x 8 galvanized grill cloth
- 1.1.3 Paint:** Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

- 1.2.1 Description:** Pan-style, self-flashing roof mounted attic exhaust vent. Features a one piece drawn dome, one piece continuous rain shield, and one piece drawn base. Brackets are riveted to the rain shield and base, and the dome is attached to brackets with screws. Screen is securely riveted in place and covers the entire vent opening. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.
- 1.2.2 Color:** Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and MILL finish.
- 1.2.3 Net Free Area:** 144 square inches per unit.
- 1.2.4 Dimensions:** Overall – 20" x 23" x 7-3/4", Opening Size – 14"
- 1.2.5 Packaging:** Packaged 2 to a carton. UPC labels are affixed to each vent and carton.
- 1.2.6 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.
- 1.2.7 Approvals:** Miami-Dade County Approved – NOA No.: 16-0510.25, expires: 08/17/2021.
Texas Department of Insurance "Windstorm" Approved – Product Evaluation Report No.: RV-22.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax