

PRODUCT SPECIFICATIONS

550 PRO G GALVANIZED ROOF LOUVER

1.2 MATERIALS:

1.2.2 Galvanized Steel:

Base: 0.017" Galvanized Steel Coiled Sheet.

Pan: 0.017" Galvanized Steel Coiled Sheet.

1.2.3 Plastic Polymers:

Collar: Custom blended, high impact co-polymer with UV stabilization additives.

1.2.4 Screen: 10 mil, 8x8 mesh Aluminum Screen.

1.1.4 Paint: Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

1.2.1 Description: Pan-style, self-flashing roof mounted attic exhaust vent. Features a weather-tight collar and large nailing flange. Screen is securely held in place for increased weather and pest protection. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and MILL finish.

1.2.3 Net Free Area: 50 square inches per unit.

1.2.4 Dimensions: Overall – 15-3/8" x 16-3/8" x 3-3/4", Hole Size – 9".

1.2.5 Packaging: Packaged 6 to a carton. UPC labels are affixed to each vent and carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax