

PRODUCT SPECIFICATIONS

865-S ROOF LOUVER

1.1 MATERIALS:

1.1.1 Plastic Polymers:

High molecular terpolymer (ABS) with UV stabilization additives.

1.1.2 Aluminum Alloy

Screen: 10 mil, 8x8 mesh Aluminum Screen.

1.2 MISCELLANEOUS:

1.2.1 Description: Injection molded, slant-back style, self-flashing roof mounted attic exhaust vent with extra tall throat for use on shake roofs. Screen and top are thermally bonded together, and the top is chemically bonded to the base. Features large nailing flange and elongated nailing slots to allow for climatic contraction or expansion. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and GRAY.

1.2.3 Net Free Area: 61 square inches per unit.

1.2.4 Dimensions: Overall – 16-1/2" x 19-3/8" x 6-11/16", Opening Size – 8-1/2" x 10-1/4"

1.2.5 Packaging: Packaged 4 to a carton. UPC labels are affixed to each vent and carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax