

# **PRODUCT SPECIFICATIONS**

## **OR-4 OMNIRIDGE SHINGLE OVER RIDGE VENT**

### **1.1 MATERIALS:**

#### **1.1.1 Plastic Polymers:**

Custom blended, high impact co-polymer with UV stabilization additives.

### **1.2 MISCELLANEOUS:**

**1.2.1 Description:** Injection molded, shingle over ridge vent. Molded in 4 foot sections. Adjustable to roof pitches from 2/12 to 16/12. Features an exterior venturi baffle with perpendicular omni baffles, internal aerodynamic curved baffles, molded end plugs, weather proof under lapping connection with alignment tabs, water shield at the louvers, and fully supported nail holes. Molded nailing lines for cap shingles. For use with 12" cap shingles. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in BLACK.

**1.2.3 Net Free Area:** 18 square inches per linear foot. (72 square inches per 4 foot part.)

**1.2.4 Packaging:** Packaged 10 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.

**1.2.5 Warranty:** Limited lifetime warranty.

**1.2.6 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.

**1.2.7 Approvals:** Miami-Dade County Approved – NOA No: 16.0510.27, expires: 08/16/21. Texas Department of Insurance "Windstorm" Approved – Product Evaluation Report No: RV-3.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax