

PRODUCT SPECIFICATIONS

TRV-4 TILERIDGE TILE ROOF RIDGE VENT

1.1 MATERIALS:

1.1.1 Plastic Polymers:

Custom blended, high impact co-polymer with UV stabilization additives.

1.2 MISCELLANEOUS:

1.2.1 Description: Injection molded, under tile ridge vent for tile roof applications using “S” profiles. Installs at the ridge pole, under the cap tile to provide a hidden ventilation solution for tile roofs. Molded in 4 foot sections. Adjustable to roof pitches from 2/12 to 8/12. Features molded end plugs, weather proof under lapping connection, water shield at the louvers, and fully supported nail holes. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BLACK.

1.2.3 Net Free Area: 18 square inches per linear foot. (72 square inches per 4 foot part.)

1.2.4 Packaging: Packaged 12 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.

1.2.5 Performance: Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.

1.2.6 Approvals: Miami-Dade County Approved – NOA No: 15-0922.06, expires: 01/06/21.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax