

# PRODUCT SPECIFICATIONS

## VUR RIDGE VENT - COPPER

### 1.1 MATERIALS:

**1.1.1 Copper Alloy:** Conforms to ASTM B152  
0.025" Copper Coiled Sheet (Embossed)

**1.1.2 Accessories:**  
End Plug: High-density polyethylene.

### 1.2 MISCELLANEOUS:

**1.2.1 Description:** Roll-formed, copper ridge vent. Adjustable to roof pitches from 3/12 to 8/12. Features a roll-formed, one-piece construction; external weather baffle; pre-punched nail holes; and male/female ends for easy connection. Embossed for durability and strength. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in COPPER

**1.2.3 Net Free Area:** 18 square inches per linear foot. (180 square inches per 10 foot part.)

**1.2.4 Packaging:** Packaged 10 to a carton. Available in 10 foot lengths. UPC labels are affixed to each vent and carton. End plug available, sold separately.

**1.2.5 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.

**1.2.6 Approvals:** Miami-Dade County Approved – NOA No: 11-0602.01, expires: 08/17/16.  
Texas Department of Insurance “Windstorm” Approved – Product Evaluation Report No: RV-13.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax