

# **PRODUCT SPECIFICATIONS**

## **150 SERIES RECTANGULAR GABLE LOUVERS**

### **1.1 MATERIALS:**

#### **1.1.1 Aluminum Alloys:** Conform to ASTM B209.

Frame: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Louvers: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Screen: 10 mil, 8x8 mesh perma-coated Aluminum Screen.

#### **1.1.2 Paint:** Factory applied baked on Valspar Super Flex.

### **1.2 MISCELLANEOUS:**

**1.2.1 Description:** Self-flashing, gable mounted attic exhaust vent. Frame is stamped, formed, and securely riveted together. Louvers are stamped, roll-formed, and mechanically tab-folded in place to the frame. Flush or recess mounted. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in BROWN, WHITE, and MILL finish.

**1.2.3 Net Free Area:** 19-285 square inches per unit.

#### **1.2.4 Dimensions:**

8x8: Overall: 10"x 10" NFA: 19 in<sup>2</sup>.

12x12: Overall: 14"x 14" NFA: 49 in<sup>2</sup>.

12x18: Overall: 14"x 20" NFA: 79 in<sup>2</sup>.

14x24: Overall: 16"x 26" NFA: 128 in<sup>2</sup>.

18x24: Overall: 20"x 26" NFA: 147 in<sup>2</sup>.

24x30: Overall: 26"x 32" NFA: 285 in<sup>2</sup>.

**1.2.5 Packaging:** Model 8x8, 12x12, 12x18, 14x24, and 18x24 units packaged 12 to a carton, model 24x30 packaged 6 to a carton. UPC labels are affixed to each vent and carton.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax

Revised on 11/14/2019