

# PRODUCT SPECIFICATIONS

## 550 PRO G GALVANIZED ROOF LOUVER

### 1.1 MATERIALS:

#### **1.1.1 Galvanized Steel:**

Base: 0.017" Galvanized Steel Coiled Sheet.

Pan: 0.017" Galvanized Steel Coiled Sheet.

#### **1.1.1 Plastic Polymers:**

Collar: Custom blended, high impact co-polymer with UV stabilization additives.

#### **1.1.3 Screen:** 10 mil, 8x8 perma-coated mesh Aluminum Screen.

#### **1.1.4 Paint:** Factory applied baked on Valspar Super Flex.

### 1.2 MISCELLANEOUS:

**1.2.1 Description:** Pan-style, self-flashing roof mounted attic exhaust vent. Features a weather-tight collar and large nailing flange. Screen is securely held in place for increased weather and pest protection. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and MILL finish.

**1.2.3 Net Free Area:** 50 square inches per unit.

**1.2.4 Dimensions:** Overall – 15-3/8" x 16-3/8" x 3-3/4", Hole Size – 9".

**1.2.5 Packaging:** Packaged 6 to a carton. UPC labels are affixed to each vent and carton.

**1.2.6 Approvals:** Texas Department of Insurance "Windstorm" Approved –  
Product Evaluation Report No.: RV-109.

**1.2.7 Other:** CSA approved for Canada.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax

Revised on 10/19/2022