

# **PRODUCT SPECIFICATIONS**

## **860-P ROOF LOUVER**

### **1.1 MATERIALS:**

#### **1.1.1 Plastic Polymers:**

Filled polypropylene with UV stabilization additives.

#### **1.1.2 Aluminum Alloy:**

Screen: 10 mil, 8x8 mesh Aluminum Screen.

### **1.2 MISCELLANEOUS:**

**1.2.1 Description:** Injection molded, slant-back style, self-flashing roof mounted attic exhaust vent. Screen and top are thermally bonded together, and the top is thermally bonded to the base. Features large nailing flange and elongated nailing slots to allow for climatic contraction or expansion. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and GRAY.

**1.2.3 Net Free Area:** 61 square inches per unit.

**1.2.4 Dimensions:** Overall – 16-1/2" x 19-3/8" x 4-3/4", Opening Size – 8-1/2" x 10-1/4"

**1.2.5 Packaging:** Packaged 6 to a carton. UPC labels are affixed to each vent and carton.

**1.2.6 Other:** CSA approved for Canada.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax

Revised on 8/19/2019