

PRODUCT SPECIFICATIONS

900 SERIES TRIANGULAR GABLE LOUVERS

1.1 MATERIALS:

1.1.1 Aluminum Alloys: Conform to ASTM B209.

Frame: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Louvers: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Screen: 10 mil, 8x8 mesh perma-coated Aluminum Screen.

1.1.2 Paint: Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

1.2.1 Description: Self-flashing, gable mounted attic exhaust vent. Louvers are stamped, roll-formed, and riveted securely in place to the frame. Adjustable from a 2.5/12 roof pitch to a 9/12 roof pitch. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, and MILL finish.

1.2.3 Net Free Area: 34-668 square inches per unit.

1.2.4 Dimensions:

904: Frame: 21-1/4", Adjustable Base: 34" – 41-5/8", NFA: 34-69 in².

905: Frame: 26-1/4", Adjustable Base: 42" – 51-3/8", NFA: 57-117 in².

906: Frame: 31-1/4", Adjustable Base: 50" – 61-1/8", NFA: 86-181 in².

907: Frame: 36-1/4", Adjustable Base: 58" – 71", NFA: 122-255 in².

908: Frame: 41-1/4", Adjustable Base: 66" – 80-3/4", NFA: 163-341 in².

909: Frame: 46-1/4", Adjustable Base: 74" – 90-1/2", NFA: 211-439 in².

910: Frame: 51-1/4", Adjustable Base: 82" – 100-3/8", NFA: 263-548 in².

911: Frame: 56-1/4", Adjustable Base: 90" – 110-1/8", NFA: 320-668 in².

1.2.5 Packaging: Packaged 1 to a carton. UPC labels are affixed to each carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 11/14/2019