

# **PRODUCT SPECIFICATIONS**

## **DA-4 DECK-AIR™ ROOF DECK INTAKE VENT**

### **1. MATERIALS:**

#### **1.1.1 Plastic Polymers:**

Custom blended, high impact co-polymer with UV stabilization additives.

#### **1.1.2 Screen:** 18 mesh Fiberglass Screen.

### **2. MISCELLANEOUS:**

**1.2.1 Description:** Injection molded, shingle over roof intake. Packaged with 30 – 2-1/2” corrosion resistant ring shank nails per part (300 per box). Molded in 4 foot sections. Can be installed on roof pitches from 3/12 to 16/12. Features unique design that provides enhanced weather protection, integrated end plugs every 2 inches, molded nail lines, and fully supported nail holes. This is an intake vent and must be used in conjunction with adequate exhaust vents for proper operation.

**1.2.2 Color:** Available in BLACK.

**1.2.3 Net Free Area:** 9 square inches per linear foot. (36 square inches per 4 foot part.)

**1.2.4 Packaging:** Packaged 10 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.

**1.2.5 Warranty:** Limited lifetime warranty.

**1.2.6 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.

**1.2.7 Approvals:** Miami-Dade County Approved – NOA No: 19-0402.01, expires: 07/10/24. Texas Department of Insurance “Windstorm” Approved – Product Evaluation Report No: RV-85.

**1.2.8 Other:** CSA approved for Canada. ICC-ES evaluated - ERS-3482 to follow IBC and IRC standards.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax

Revised on 8/19/2019