

PRODUCT SPECIFICATIONS

OR4-S OMNIRIDGE SHINGLE OVER RIDGE VENT

1.1 MATERIALS:

1.1.1 Plastic Polymers:

Custom blended, high impact co-polymer with UV stabilization additives.

1.2.1 Screen: 18 mesh Fiberglass Screen.

1.2 MISCELLANEOUS:

1.2.2 Description: Injection molded, shingle over ridge vent. Molded in 4 foot sections. Adjustable to roof pitches from 2/12 to 16/12. Features an exterior venturi baffle with perpendicular omni baffles, internal aerodynamic curved baffles, molded end plugs, weather proof under lapping connection with alignment tabs, water shield at the louvers, and fully supported nail holes. Additional screen for increased weather protection. Molded nailing lines for cap shingles. For use with 12" cap shingles. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.3 Color: Available in BLACK.

1.2.4 Net Free Area: 18 square inches per linear foot. (72 square inches per 4 foot part.)

1.2.5 Packaging: Packaged 10 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.

1.2.6 Warranty: Limited lifetime warranty.

1.2.7 Approvals: Miami-Dade County Approved – NOA No: 21-0323.08, expires: 08/16/2026.
Texas Department of Insurance "Windstorm" Approved – Product Evaluation Report No: RV-3.

1.2.8 Other: CSA approved for Canada.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 8/31/2021