

# **PRODUCT SPECIFICATIONS**

## **PCV-1 POWERED CRAWLSPACE VENT**

### **1.1 MATERIALS:**

#### **1.1.1 Plastic Polymers:**

Mounting Plate: 0.125" Filled polypropylene with UV stabilization additives.

#### **1.1.2 Galvanized Steel:**

Electrical Control Box: 0.036" Galvanized Steel Coiled Sheet.

### **1.2 MISCELLANEOUS:**

**1.2.1 Description:** Powered foundation vent for providing fresh air ventilation to a crawl space. Designed to mount behind existing 8" x 16" foundation vent. Three prong, grounded plug for safety and convenience.

**1.2.2 Color:** Available in BLACK finish.

**1.2.3 Fan:** 110 CFM electric case fan.

**1.2.4 Thermostat/Humidistat:** Preset thermostat turns off at 40°F and on at 50°F or higher. The humidistat is preset to 60% RH and is adjustable from 20% RH to 80% RH. Includes thermal protection for safety.

**1.2.5 Dimensions:** 9" x 19" x 3"

**1.2.6 Packaging:** Packaged 6 to a carton. UPC labels are attached to each vent and carton.

**1.2.7 Performance:** UL listed(GPWX.E44479).

**1.2.8 Other:** CSA approved for Canada.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax

Revised on 8/19/2019