

PRODUCT SPECIFICATIONS

150 SERIES RECTANGULAR GABLE LOUVERS

1.1 MATERIALS:

1.1.1 Aluminum Alloys: Conform to ASTM B209.

Frame: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Louvers: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Screen: 10 mil, 8x8 perma-coated mesh Aluminum Screen.

1.1.2 Paint: Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

1.2.1 Description: Self-flashing, gable mounted attic exhaust vent. Frame is stamped, formed, and securely riveted together. Louvers are stamped, roll-formed, and mechanically tab-folded in place to the frame. Flush or recess mounted. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, and MILL finish.

1.2.3 Net Free Area: 19-285 square inches per unit.

1.2.4 Dimensions:

8x8: Overall: 10"x 10" NFA: 19 in².

12x12: Overall: 14"x 14" NFA: 49 in².

12x18: Overall: 14"x 20" NFA: 79 in².

14x24: Overall: 16"x 26" NFA: 128 in².

18x24: Overall: 20"x 26" NFA: 147 in².

24x30: Overall: 26"x 32" NFA: 285 in².

1.2.5 Packaging: Model 8x8, 12x12, 12x18, 14x24, and 18x24 units packaged 12 to a carton, model 24x30 packaged 6 to a carton. UPC labels are affixed to each vent and carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 10/19/2022