

PRODUCT SPECIFICATIONS

730 ROOF LOUVER

1.1 MATERIALS:

1.1.1 Aluminum Alloys: Conform to ASTM B209.

Base: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Sides: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Top: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Collar: 0.0175" Aluminum Coiled Sheet.

1.1.2 Paint: Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

1.2.1 Description: Slant-back style, self-flashing roof mounted attic exhaust vent. Features a bird-proof construction, louvered sides are seamed to the top and the top is riveted securely to the base flashing; three louvered sides open upward to prevent shingle discoloration; weather-tight collar, seamed to the base flashing; and large nailing flange. Painted units are embossed for extended paint life, durability, and blended appearance with shingles. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and MILL finish.

1.2.3 Net Free Area: 30 square inches per unit.

1.2.4 Dimensions: Overall – 12-3/16" x 17-3/4" x 4", Hole Size – 6-1/4".

1.2.5 Packaging: Packaged 6 to a carton. UPC labels are affixed to each vent and carton.

1.2.6 Performance: Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.

1.2.7 Approvals: Miami-Dade County Approved – NOA No: 21-0629.02, expires: 08/16/2026.
Texas Department of Insurance "Windstorm" Approved – Product Evaluation Report No: RV-11.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 8/31/2021