

PRODUCT SPECIFICATIONS

750-GES GALVANIZED ROOF LOUVER

1.1 MATERIALS:

1.1.1 Galvanized Steel:

Base: 0.017" Galvanized Steel Coiled Sheet.

Sides: 0.017" Galvanized Steel Coiled Sheet.

Top: 0.017" Galvanized Steel Coiled Sheet.

Collar: 0.015" Galvanized Steel Coiled Sheet.

1.1.2 Screen: 16x18 mesh Aluminum Screen.

1.1.3 Paint: Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

1.2.1 Description: Slant-back style, self-flashing roof mounted attic exhaust vent. Features a bird-proof construction, louvered sides are seamed to the top and the top is riveted securely to the base flashing; three louvered sides open upward to prevent shingle discoloration; weather-tight collar, seamed to the base flashing; and large nailing flange. Additional screen for increased weather protection. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and MILL finish.

1.2.3 Net Free Area: 50 square inches per unit.

1.2.4 Dimensions: Overall – 23" x 27-1/4" x 5", Hole Size – 8".

1.2.5 Packaging: Packaged 4 to a carton. UPC labels are affixed to each vent and carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 11/2/2023