

# **PRODUCT SPECIFICATIONS**

## **A-SERIES TRIANGULAR GABLE LOUVERS**

### **1.1 MATERIALS:**

#### **1.1.1 Aluminum Alloys:** Conform to ASTM B209.

Frame: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Louvers: 0.025" Aluminum Coiled Sheet. (Embossed on painted units)

Screen: 10 mil, 8x8 perma-coated mesh Aluminum Screen.

#### **1.1.2 Paint:** Factory applied baked on Valspar Super Flex.

### **1.2 MISCELLANEOUS:**

**1.2.1 Description:** Self-flashing, gable mounted attic exhaust vent. Louvers are stamped, roll-formed, and riveted securely in place to the frame. Adjustable from a 6/12 roof pitch to a 12/12 roof pitch. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in BROWN, WHITE, and MILL finish.

**1.2.3 Net Free Area:** 46-142 square inches per unit.

#### **1.2.4 Dimensions:**

A50B: Frame: 20-3/8", Adjustable Base: 28-7/8" – 36-3/8", NFA: 46-60 in<sup>2</sup>.

A56B: Frame: 23-7/8", Adjustable Base: 33-3/4" – 42-7/8", NFA: 71-100 in<sup>2</sup>.

A88B: Frame: 27-9/16", Adjustable Base: 39" – 49-3/8", NFA: 81-142 in<sup>2</sup>.

**1.2.5 Packaging:** Packaged 1 to a carton. UPC labels are affixed to each carton.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax

Revised on 10/19/2022