

PRODUCT SPECIFICATIONS

CV-SERIES UNDEREAVE CIRCLE VENT

1.1 MATERIALS:

- 1.1.1 Aluminum Alloys:** Conform to ASTM B209.
0.019" Aluminum Coiled Sheet.
Screen: 10 mil, 18x16 mesh Aluminum Screen.
- 1.1.2 Paint:** Factory applied baked on Valspar Super Flex.

1.2 MISCELLANEOUS:

- 1.2.1 Description:** Under eave mounted attic intake vent. Louvers are stamped and formed, and the screen is securely held in place. This is an intake vent and must be used in conjunction with adequate exhaust vents for proper operation.
- 1.2.2 Color:** Available in BROWN, WHITE, and MILL finish.
- 1.2.3 Net Free Area:** 0.23" – 3" square inches per unit.
- 1.2.4 Dimensions:**
CV-1: 1-1/4" Dia., NFA: 0.23 in².
CV-2: 2-1/4" Dia., NFA: 1.5 in².
CV-3: 3-1/2" Dia., NFA: 2.57 in².
CV-4: 4-1/2" Dia., NFA: 3 in².
- 1.2.5 Packaging:** Models CV-1, CV-2, CV-3 are packaged 6 units per bag, with 12 bags in a master carton (72 total units). Model CV-4 is packaged 36 individual pieces per master carton. UPC labels are affixed to each bag and carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 11/14/2019