

PRODUCT SPECIFICATIONS

P60 PRO ROOF LOUVER

1.1 MATERIALS:

- 1.1.1 Plastic Polymers:** Custom blended, high impact co-polymer with UV stabilization additives.
- 1.1.2 Screen:** 10 mil, 18x16 mesh Aluminum Screen.

1.2 MISCELLANEOUS:

- 1.2.1 Description:** Pan-style, self-flashing roof mounted attic exhaust vent. Features a weather-tight collar and large nailing flange. Screen is securely held in place for increased weather and pest protection. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.
- 1.2.2 Color:** Available in BROWN, WHITE, BLACK, WEATHERED BRONZE, and GRAY.
- 1.2.3 Net Free Area:** 60 square inches per unit.
- 1.2.4 Dimensions:** Overall – 15-5/8” x 16” x 4-3/8”, Hole Size – 9”x 9”.
- 1.2.5 Packaging:** Packaged 6 to a carton. UPC labels are affixed to each vent and carton.
- 1.2.6 Performance:** Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.
- 1.2.7 Approvals:** Miami-Dade County Approved – NOA No: 23-1016.03, expires: 12/20/28. Texas Department of Insurance “Windstorm” Approved – Product Evaluation Report No: RV-110.
- 1.2.8 Other:** CSA approved for Canada.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax

Revised on 12/18/2023