

## **750-GES ROOF VENT**

**ENHANCED WEATHER PROTECTION** 



## THE IDEAL DORMER VENT 750-GES FEATURES:

- Galvanized steel construction.
- Enhanced weather protection.
- Extra large 6" nailing flange.
- 1/16" nominal mesh screen.
- Fits 2/12 to 16/12 roof pitch.
- Weather proof and bird proof.
- Design prevents roof discoloration.
- Stack effect and three louvered sides provide enhanced airflow.



**The Lomanco 750-GES Roof Vent** is built with three outward and upward discharging side vents to prevent unsightly roof streaking that is so common with ordinary roof louvers. This exclusive Lomanco design also prevents the problem of bird and animal infiltration while providing maximum attic exhaust air flow and weather protection.

## **PREVENTS UNSIGHTLY ROOF DISCOLORATION**

Available Colors:





Weathered Bronze

Model	Overall Size (in.)	Opening Size (in.)	NFA (in. <sup>2</sup> )
750-GES	23 x 27¼ x 5	8	50

1	ATTIC FLOOR SPACE IN SQ FT:	1000						1500									2000									2500								3000									3500							
		Intake						Intake								Intake								Intake							Intake								Intake											
	EXHAUST SYSTEM	Exhaust	C416	C616	5		105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	8	SV-10 DA-4/IV-9	
	750-GES	5	10	7	4	4	4	3	4	7	8	16	11	7	6	5	7	12	10	20	14	8	7	6	8	14	12	24	17	10	9	7	10	17	15	30	21	12	11	9	12	21	17	34	23	14	12	0	14 24	1

How many vents do you need? Select the Attic Floor Space to be ventilated and an Exhaust System — find where the two intersect to determine the amount of **750** -GES vents needed. Select an Intake System and repeat the steps to determine the amount of intake vents needed.