

P60 PRO

ADVANCED FEATURE PLASTIC ROOF VENT



P60 PRO FEATURES:

- Patented design. See Imcpat.com
- Inner guard stops pest intrusion.
- 18" x 16" mesh screen for enhanced weather protection.
- Low profile design.

Available Colors:

• Designed for fast installation.

WH

• Pure impact-resistant polypropylene will not dent or crack in extreme heat or cold installations.

GR

- Additives provide superior resistance to fading and UV degradation.
- Same tried and proven polypropylene material as Lomanco Omni Series ridge vents.
- Lifetime Limited Warranty.







Model	Overall Size (in.)	Opening Size (in.)	NFA (in. ²)
P60 PRO	15% x 1515/16 x 43%	9	60

ATTIC FLOOR SPACE IN SQ FT:	1000					1500										2	00	0			2500									3000								3500										
	Intake						Intake						Intake								Intake							Intake							Intake													
EXHAUST SYSTEM	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	오	-10	DA-4/IV-9
P60 PRO	4	10	7	4	4	3	4	7	6	15	10	6	5	5	6	10	8	20	13	8	7	6	8	14	10	24	17	10	9	7	10	17	12	29	20	12	10	9	12	20	14	34	23	13	12	10	14	24

How many vents do you need? Select the Attic Floor Space to be ventilated and an Exhaust System — find where the two intersect to determine the amount of P60 PRO vents needed. Select an Intake System and repeat the steps to determine the amount of intake vents needed.