TileRica OMANCO **Functional Ridge Vent for Tile Roof! Installed Section View** Cap Tile Ridge Board Mortar or TRV-4 TRV-4 Weather Blocking Material Mortar or Weather Blocking Material **Roof Tile Roof Tile** Batton Decking Rafter **Ventilation Cutout**

TRV-4 FEATURES:

- Functional and concealed ventilation installed under the cap tile.
- Excellent airflow design with superior weather protection and no filter to clog.
- ▶ Tough durable construction.
- Bottom integrated hinged flange adjusts from 2/12 to 8/12 roof pitches.

- Works on high & medium profile "S" tile roofs with 2"x 6" ridge pole.
- Interlocking self alignment design with weatherproof over lapping joint.
- Works with mortar or other approved weather blocking material.
- 18" net free area per linear foot of installed vent (9 sq. inches per side).
- Internal water shield.

- Molded-in weep openings, nail holes and end plug.
- Cut line provided for two foot lengths.
- Engineered material guarantees longevity.
- Patented design.
- 30 year transferable warranty.

TRV-4 Tile Roof Vent Specifications

NFA	Color	Length	Roof	Carton		
(in.2)		(ft.)	Pitch	Quantity		
18 Per Linear Foot (9 per side).	Black	4	2/12 to 8/12	12		



Want more info? Scan this QR code with your smartphone.



How many Tile Vents do you need?

F =	Attic floor space to be ventilated in square feet:											
CS	1000		1500		2000		2500		3000		3500	
ΑĖ		Intake		Intake		Intake		Intake		Intake		Intake
EXH	Exhaust	6- / I	Exhaust	6-VI	Exhaust	6-VI	Exhaust	6- / I	Exhaust	6-/1	Exhaust	6- / I
TRV-4	28'	7	40'	10	54'	14	68'	17	80'	20	94'	24

MADE IN USA LO456_1220

